

PH280 – WATER BLAST 30

 polyhose.com/products/rubber-hose/ph280-water-blast-30/

Application

Water blasting, Water jetting, cleaning, cleaning equipment. Delivery of water and water emulsions.



Code	Dash size	DN	Hose I.D. (Nom.)		Reinforcement O.D (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Part#			inch	mm	inch	mm	psi	bar	psi	bar	psi	bar	mm	inch
PH280-4	-4	6	1/4	6.4	0.58	14.7	0.71	17.9	12325	850	30810	2125	130	5.12
PH280-6	-6	10	3/8	9.5	0.69	17.5	0.843	21.4	12325	850	30810	2125	155	6.10
PH280-8	-8	12	1/2	12.7	0.80	20.2	0.97	24.6	12325	850	30810	2125	200	7.87
PH280-12	-12	20	3/4	19.0	1.17	29.8	1.29	32.8	12325	850	30810	2125	250	9.84
PH280-16	-16	25	1	25.4	1.58	40.2	1.76	44.6	12325	850	30810	2125	300	11.81

Applicable Standard:

Standard: Manufacturers Design

Construction:

Core: Oil resistant Synthetic rubber

Reinforcement: 4 [up to DN 25] or 6 high tensile steel spirals

Cover: Black Color, Synthetic rubber resistant to oil, weather and abrasion

Temperature Range:

Continuous: -40°C to +100°C

Intermittant: max. +120°C

Copyright © Polyhose. All rights reserved. Powered by [DigitFellas](#)