

PH534 – LPG Hose TypeD

 polyhose.com/products/rubber-hose/ph534-lpg-hose-typed/

Application

Designed for transfer of LPG in liquid or gaseous phase and natural gas.



Code	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
	inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH534-8	1/2	12.7	0.90	22.7	363	25	1452	100	100	4.00
PH534-10	5/8	16.0	1.02	25.9	363	25	1452	100	127	5.00
PH534-12	3/4	19.0	1.22	31	363	25	1452	100	160	6.30
PH534-16	1	25.4	1.25	38.1	363	25	1452	100	200	8.00
PH534-20	1.1/4	31.8	1.77	45	363	25	1452	100	250	9.84
PH534-24	1.1/2	38.1	2.05	52	363	25	1452	100	320	12.60
PH534-32	2	50.8	2.64	67	363	25	1452	100	400	45.75

Applicable Standard:

Standard: EN 1762 – Type D

Construction:

Core: Low Permeation Synthetic rubber tube resistant to n-pentane

Reinforcement: Single wire braid.

Cover: Perforated orange outer cover resistant to ozone, abrasion resistance

Temperature Range:

Continuous: -40°C to +80°C

Copyright © Polyhose. All rights reserved. Powered by [DigitFellas](#)