

PH155 – Triflex

 polyhose.com/products/rubber-hose/ph155-triflex/

Application

High Pressure for forest industry. Compatible with mineral, vegetable oils, glycol, polyglycol based, synthetic ester based oils, oils in water emulsion, water.



Code	DN	Hose I.D. (Nom.)		Reinforcement O.D (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
		inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH155-6	10	3/8	9.5	17.7	0.697	21.3	0.839	500	7250	2000	29000	180	7.09
PH155-8	12	1/2	12.7	20.5	0.807	24.3	0.957	470	6815	1880	27260	230	9.06
PH155-10	16	5/8	16.0	24.4	0.961	28.0	1.102	410	5945	1640	23780	250	9.84
PH155-12	20	3/4	19.0	27.8	1.094	31.5	1.240	375	5435	1500	21750	300	11.81
PH155-16	25	1	25.4	34.7	1.366	38.7	1.524	315	4565	1260	18270	340	13.39

Applicable Standard:

Standard: Manufacturers Design

Construction:

Core: Smooth synthetic rubber resistant to oils and water

Reinforcement: 3 high tensile steel braids

Cover: Synthetic rubber resistant to oils and ozone

Temperature Range:

Continuous: -40°C to +100°C

Intermittent: max. +120°C

Copyright © Polyhose. All rights reserved. Powered by [DigitFellas](#)