

PH471 – Steam 1 W/B

 polyhose.com/products/rubber-hose/ph471-steam-1-wb/

Application

High temperature steam lines at constant pressure of 150 psi.



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
			inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH471-8	-8	12	1/2	12.7	0.87	22.0	150	10	1500	100	175	7.0
PH471-12	-12	20	3/4	19.0	1.14	29.0	150	10	1500	100	240	9.6
PH471-16	-16	25	1	25.4	1.37	34.8	150	10	1500	100	300	12.0
PH471-20	-20	32	1.1/4	31.8	1.65	42.0	150	10	1500	100	400	16.0

Red Colour Cover also available.

Applicable Standard:

Standard: IS 10655 Type 2 / BS 5342

Construction:

Core: EPDM rubber resistant high temperature steam

Reinforcement: Single steel wire braid

Cover: Black Color, EPDM rubber resistant to abrasion, heat and weather

Temperature Range:

Continuous: up to +185°C

Copyright © Polyhose. All rights reserved. Powered by [DigitFellas](#)