

PH472 – Steam 2 WB

 polyhose.com/products/rubber-hose/ph472-steam-2-wb/

Application

High temperature steam lines at constant pressure of 250 psi.



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
			inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH472-8	-8	12	1/2	12.7	0.91	23.0	210	18	2600	180	175	7.0
PH472-12	-12	20	3/4	19.0	1.18	30.0	210	18	2600	180	240	9.6
PH472-16	-16	25	1	25.4	1.45	36.8	210	18	2600	180	300	12.0
PH472-20	-20	32	1.1/4	31.8	1.71	43.5	210	18	2600	180	400	16.0
PH472-24	-24	38	1/2	38.1	1.95	49.5	210	18	2600	180	500	20.0
PH472-32	-32	50	2	50.8	2.52	64.0	210	18	2600	180	625	25.0
PH472-40	-40	63	2.1/2	63.0	3.26	83.0	210	18	2600	180	675	27.0
PH472-48	-48	76	3	76.0	3.85	98.0	210	18	2600	180	725	29.0

Red Colour Cover also available.

Applicable Standard:

Standard: IS 10655 Type 3/BS 5342.

Construction:

Core: EPDM rubber resistant high temperature steam

Reinforcement: Double steel wire braids

Cover: Black color, EPDM rubber resistant to abrasion, heat and weather

Temperature Range:

Upto +210°C

Copyright © Polyhose. All rights reserved. Powered by [DigitFellas](#)