

# PH501 – 134 NB Type

 [polyhose.com/products/rubber-hose/ph501-134-nb-type/](https://polyhose.com/products/rubber-hose/ph501-134-nb-type/)

## Application

Automotive Air-Conditioning System Recommended Fluids: Freon R 134a and Pag lubricant oils.



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Part#			inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH501-8	-8	10.5	13/32	10.5	0.874	22.0	497	34	2610	180	70	2.80
PH501-10	-10	12	1/2	12.7	0.969	24.6	497	34	2610	180	76	3.00
PH501-12	-12	16	5/8	16.0	1.060	28.1	497	34	2610	180	81	3.20

Applicable Standard:

**Standard:** SAE J 2064 Type A

Construction:

**Core:** Synthetic Rubber resistant to Freon 134a and pag oils

**Reinforcement:** High tensile textile fiber

**Cover:** Black color, Synthetic rubber resistant to oil and recommended for application at very high temperature.

Temperature Range:

**Continuous:** 35°C to +125°C **Intermittent:** max. +135°C