

PH303/PH304 – Sewer Jet 4000 PSI

 polyhose.com/products/thermoplastic-hose/ph-303ph-304-sewer-jet-4000-psi/

Application

Compact Sewer cleaning vehicles and lateral Sewer line cleaning equipments.

Heavy duty construction for optimum cut and wear resistance. Bonded tube and cover available in long lengths with a special cover, resistant to microbiological degradation. High pressure performance and flexible hose for cleaning smaller sized sewer ducts



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Part#			inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH303-3	-3	5	3/16	4.8	0.405	10.3	4000	280	12000	840	40	1.6
PH303-4	-4	6	1/4	6.4	0.500	12.7	4000	280	12000	840	40	1.6
PH303-6	-5	10	3/8	9.5	0.670	17.0	4000	280	12000	840	75	3.0
PH303-8	-8	12	1/2	12.7	0.920	23.4	4000	280	12000	840	75	3.0
PH304-8	-8	12	1/2	12.7	0.800	20.3	4000	280	16000	1120	100	4.0
PH303-12	-12	20	3/4	19.0	1.150	29.2	3600	250	9000	625	125	5.0
PH303-16	-16	25	1	25.4	1.500	37.9	3600	250	9000	625	160	6.4
PH303-20	-20	32	1.1/4	31.8	1.800	45.7	3600	250	9000	625	250	10.0

Applicable Standard:

Standard: ISO7751

Construction:

Core: Thermoplastic Elastomer

Reinforcement: 1 or 2 braids of synthetic fibre / Aramid Fiber + 1 special synthetic fiber braid

Cover: Green color – polyurethane.

Temperature Range:

Continuous: -40°C to +60°C

Copyright © Polyhose. All rights reserved. Powered by [i-Vertys](#)