


# PH305 – Sewer Jet 2800 PSI

 [polyhose.com/products/thermoplastic-hose/ph-305-sewer-jet-2800-psi/](https://polyhose.com/products/thermoplastic-hose/ph-305-sewer-jet-2800-psi/)

## Application

Standard Sewer cleaning vehicles and cleaning equipments.

Special construction for better flexibility and wear resistance. Bonded tube and cover. Available in long lengths with a special cover, resistant to microbiological degradation. Lightweight compared to conventional rubber alternatives and increased lifetime.



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Part#			inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH305-8	-8	12	1/2	12.8	0.810	20.6	2800	190	7000	480	100	4.0
PH305-12	-12	20	3/4	19.2	1.150	29.2	2800	190	7000	480	125	5.0
PH305-16	-16	25	1	25.5	1.450	36.8	2800	190	7000	480	160	6.4

Applicable Standard:

**Standard:** ISO7751

Construction:

**Core:** Thermoplastic Elastomer

**Reinforcement:** 1Braid of Synthetic Fiber and 1 special synthetic fibre armouring

**Cover:** Yellow Color – Polyurethane

Temperature Range:

**Continuous:** 40°C to +60°C

Copyright © Polyhose. All rights reserved. Powered by [i-Vertys](#)