

PH346 – Paint Spray

 polyhose.com/products/thermoplastic-hose/ph346-paint-spray/

Application

High pressure Airless paint spray system for 245 to 350 Bar.

Suitable for applications requiring chemical resistance to solvents and aggressive fluids.



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
			inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH346-3	-3	5	3/16	4.8	0.405	10.3	5000	350	20000	1400	50	2.0
PH346-4	-4	6	1/4	6.4	0.490	12.4	5000	350	20000	1400	75	3.0
PH346-6	-6	10	3/8	9.5	0.620	15.7	4350	300	17400	1200	100	4.0
PH346-8	-8	12	1/2	12.7	0.760	19.3	3500	245	14000	980	120	4.8

Applicable Standard:

Standard: Polyhose proprietary product.

Construction:

Core: Polyamide

Reinforcement: 1 or 2 Braids of aramid fibre with anti-static polymeric layer

Cover: Blue color, Pin pricked Polyurethane and other colors on request.

Temperature Range:

Continuous: -40°C to +100°C Temp not to exceed +70°C for Air and water based fluids.

Copyright © Polyhose. All rights reserved. Powered by [i-Vertys](#)