

PH522 – SUPER SERVICE HOSE

 polyhose.com/products/rubber-hose/ph522-super-service-hose/

Application

Cleaning lines for hobby and semi-professional machines. High flexibility for use with mineral, glycols, polyglycols oils, syntetic ester based oils, oils in water emulsion, water.



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Part#			inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH522-4	-4	6	1/4	6.4	0.59	15.0	9,425	650	23,200	1,600	100	4.00
PH522-5	-5	8	5/16	8.0	0.64	16.6	7,975	550	20,300	1,400	115	4.60
PH522-6	-6	10	3/8	9.5	0.75	19.0	7,610	525	19,140	1,320	125	5.00
PH522-8	-8	12	1/2	12.7	0.87	22.2	6,380	440	15,940	1,100	180	7.10

Applicable Standard:

Standard: EN 853 – 2 SN

Construction:

Core: Oil & Water Resistant Synthetic rubber

Reinforcement: Two High Tensile Steel Wire Braid.

Cover: Synthetic rubber resistant to Oil, Ozone. Colour Grey / Blue on request.

Temperature Range:

Continuous: -40°C to +155°C

Copyright © Polyhose. All rights reserved. Powered by [DigitFellas](#)