

PH532 – SAEJ30R6 TYPE3

 polyhose.com/products/rubber-hose/ph532-saej30r6-type3/

Application

Low Pressure Coupled and Uncoupled low- permeation Fuel Hose for Automotive and allied applications. Physical, Extractable and fuel permeation properties as specified in SAE J 30 – R6 Standard for use with gasoline, diesel fuel, lubrication oil, or the vapour present in either fuel system or in crank case of internal combustion engines



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Min. Burst Pressure		Min. Bend Radius	
			inch	mm	inch	mm	psi	bar	mm	inch
PH532-3	-3	5	3/16	4.8	0.41	10.3	250	17.2	50	2.00
PH532-4	-4	6	1/4	6.4	0.50	12.7	250	17.2	65	2.60
PH532-5	-5	8	5/16	8.0	0.56	14.3	250	17.2	75	3.00
PH532-6	-6	10	3/8	9.5	0.62	15.8	250	17.2	75	3.00
PH532-8	-8	12	1/2	12.7	0.78	19.8	175	12.0	100	4.00
PH532-10	-10	16	5/8	16.0	0.93	23.8	175	12.0	125	5.00
PH532-12	-12	19	3/4	19.0	1.12	28.5	175	12.0	150	6.00

Applicable Standard:

Standard: SAE J 30 R6 TYPE 3

Construction:

Core: Oil and Fuel resistant Synthetic rubber.

Reinforcement: Single braided ply of textile.

Cover: Black Color, Synthetic rubber resistant to oil, ozone

Temperature Range:

Continuous: -40°C to +100°C

Copyright © Polyhose. All rights reserved. Powered by [DigitFellas](#)