

# PH535 – LPG Hose Type2

 [polyhose.com/products/rubber-hose/ph535-lpg-hose-type2/](https://polyhose.com/products/rubber-hose/ph535-lpg-hose-type2/)

## Application

Designed for use in motor vehicles with liquified petroleum Gas (LPG) installations.



Code	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
	Part#	inch	mm	inch	mm	psi	bar	psi	bar	mm
PH535-4	1/4	6.4	0.50	12.7	363	25	1452	100	70	2.76
PH535-5	5/16	8.0	0.60	15.3	363	25	1452	100	95	3.74
PH535-6	3/8	9.5	0.66	16.9	363	25	1452	100	120	4.72
PH535-8	1/2	12.7	0.82	20.8	363	25	1452	100	150	5.91
PH535-10	5/8	16.0	0.92	23.5	363	25	1452	100	185	7.28
PH535-12	3/4	19.0	1.04	26.5	363	25	1452	100	225	8.86

Applicable Standard:

**Standard:** Propriety

Construction:

**Core:** Low Permeation Synthetic rubber tube resistant to n-pentane

**Reinforcement:** Single Synthetic Yarn with electrically bonded wire optional

**Cover:** Perforated outer cover resistant to ozone.

---

Temperature Range:

**Continuous:** -40°C to +80°C

---

Copyright © Polyhose. All rights reserved. Powered by [DigitFellas](#)