


# PH301- Sewer Jet 2500 PSI

 [polyhose.com/products/thermoplastic-hose/ph-301-sewer-jet-2500-psi/](https://polyhose.com/products/thermoplastic-hose/ph-301-sewer-jet-2500-psi/)

## Application

Standard Sewer Cleaning vehicles and cleaning equipments

Special construction for optimum cut and wear resistance. Bonded tube and cover. Available in long lengths with a special cover resistant to microbiological degradation. Lightweight compared to conventional rubber alternatives and increased lifetime.



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Part#			inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH301-3	-3	5	3/16	4.8	0.410	10.41	2500	175	6250	438	40	1.6
PH301-4	-4	6	1/4	6.4	0.490	12.4	2500	175	6250	438	40	1.6
PH301-6	-6	10	3/8	9.5	0.630	16.0	2500	175	6250	438	60	2.4
PH301-8	-8	12	1/2	12.7	0.810	20.6	2500	175	6250	438	100	4.0
PH301-12	-12	20	3/4	19.0	1.150	29.2	2500	175	6250	438	125	5.0
PH301-16	-16	25	1	25.4	1.450	36.8	2500	175	6250	438	160	6.4
PH301-20	-20	32	1.1/4	31.8	1.800	45.7	2500	175	6250	438	250	10.0

Applicable Standard:

**Standard:** ISO7751

---

Construction:

**Core:** Thermoplastic Elastomer

**Reinforcement:** 1 or 2 braids of synthetic fibre

**Cover:** Orange color – polyurethane.

---

Temperature Range:

**Continuous:** -40°C to +60°C

---

Copyright © Polyhose. All rights reserved. Powered by [i-Vertys](#)